

Slim Line Series (SL Series)

Our Slim Line units are designed for those applications where space is at a premium. With their slim line stance, these units are ideal for racks, cabinets and workbenches. The 20 Amp models are offered complete with 20 Amp circuit breaker, 20 Amp wiring, and 15/20 Amp outlets.



Features

- Push to reset Circuit Breaker
- 15Amp, (UL 1363) and 12 Amp (UL 60950)
- 20Amp,(UL 1363) and 16Amp (UL 60950)
- (UL 1363/UL 60950) Approved
- Streamlined Slim Aluminum Stance
- Grey Finish
- Spring Clip Mounting

[Printable PDF](#)



Model No.	Outlets	Outlet Spacing Ctr to Ctr	On/Off Switch	Cord Length	Amps	Dimensions
15 Amps - UL1363, 12 Amps - UL60950						
SL 24-8-6	8	2 1/2"	No	6'	15/12	24" x 1 1/2" x 1 3/16"
SL 24-8-15	8	2 1/2"	No	15'	15/12	24" x 1 1/2" x 1 3/16"
SL 36-10-6	10	2 1/2"	No	6'	15/12	36" x 1 1/2" x 1 3/16"
SL 36-10-15	10	2 1/2"	No	15'	15/12	36" x 1 1/2" x 1 3/16"
SL 48-12-6	12	3 1/2"	No	6'	15/12	48" x 1 1/2" x 1 3/16"
SL 48-12-15	12	3 1/2"	No	15'	15/12	48" x 1 1/2" x 1 3/16"
SL 72-15-6	15	4 1/2"	No	6'	15/12	72" x 1 1/2" x 1 3/16"
SL 72-15-15	15	4 1/2"	No	15'	15/12	72" x 1 1/2" x 1 3/16"
20 Amps - UL1363, 16 Amps - UL60950						
SL 24-8-6 (20A)	8	2 1/2"	No	6'	20/16	24" x 1 1/2" x 1 3/16"
SL 24-8-15 (20A)	8	2 1/2"	No	15'	20/16	24" x 1 1/2" x 1 3/16"
SL 36-10-6 (20A)	10	2 1/2"	No	6'	20/16	36" x 1 1/2" x 1 3/16"
SL 36-10-15 (20A)	10	2 1/2"	No	15'	20/16	36" x 1 1/2" x 1 3/16"
SL 48-12-6 (20A)	12	3 1/2"	No	6'	20/16	48" x 1 1/2" x 1 3/16"
SL 48-12-15 (20A)	12	3 1/2"	No	15'	20/16	48" x 1 1/2" x 1 3/16"
SL 72-15-6 (20A)	15	4 1/2"	No	6'	20/16	72" x 1 1/2" x 1 3/16"
SL 72-15-15 (20A)	15	4 1/2"	No	15'	20/16	72" x 1 1/2" x 1 3/16"

Optional: Switch (S), Twist Lock (TL), Pilot Light (PL)
 Custom units from 6" to 77" with max of 24 outlets



'X' MAY VARY FROM
6 INCHES TO 77 INCHES

